

Specifications

Models	AWP-30S	
Measurements	US	Metric
Working height*	35 ft 6 in	11.00 m
Platform height	29 ft 6 in	9.00 m
A Height - stowed (Standard)	6 ft 6 in	1.98 m
stowed (RT/Narrow)	6 ft 7 in	2.01 m
B tilted back** (Standard)	_____	_____
C Length - stowed (Standard)	4 ft 5 in	1.35 m
stowed (RT/ Narrow)	5 ft 3 in	1.60 m
D Length - tilted back**	_____	_____
E Width (Standard)	2 ft 5 in	.74 m
Width (RT)	2 ft 6 in	.76 m
Width (Narrow)	1 ft 11 in	.58 m
Lift capacity	350 lbs	159 kg
ANSI/CSA:		
F G Outrigger footprint (l/w) (Standard)	5 ft 9 in/5 ft 1 in	1.75/1.55 m
Outrigger footprint (l/w) (RT/Narrow)	6 ft/5 ft	1.83/1.52 m
H Corner access*** (Standard)	1 ft 7 in	.48 m
Corner access*** (RT/Narrow)	1 ft 7 in	.48 m
I J Wall access front/side (Standard)	5 in/1 ft 5 in	.13/.43 m
Wall access front/side (RT/Narrow)	7 in/1 ft 5 in	.18/.43 m
CE/AUS/PB Indoor:		
F G Outrigger footprint (l/w) (Standard)	6 ft 4 in/5 ft 8 in	1.93/1.73 m
Outrigger footprint (l/w) (RT/Narrow)	6 ft 11 in/6 ft 2 in	2.11/1.88 m
H Corner access*** (Standard)	1 ft 10 in	.56 m
Corner access*** (RT/Narrow)	2 ft 3.5 in	.70 m
I J Wall access front/side (Standard)	8 in/1 ft 9 in	.20/.53 m
Wall access front/side (RT/Narrow)	9 in/1 ft 8 in	.23/.51 m
CE/AUS/PB Outdoor:		
F G Outrigger footprint (l/w) (Standard)	9 ft 9 in/9 ft 2 in	2.97/2.79 m
Outrigger footprint (l/w) (RT/Narrow)	10 ft 10 in/11 ft 4 in	3.30/3.45 m
H Corner access*** (Standard)	2 ft 3 in	.69 m
Corner access*** (RT/Narrow)	5 ft 1 in	1.55 m
I J Wall access front/side (Standard)	2 ft 3 in/3 ft 6 in	.69/1.07 m
Wall access front/side (RT/Narrow)	2 ft 11 in/4 ft 7 in	.89/1.40 m
Platform Dimensions: (l/w/h)		
Standard	27/26/44.75 in	.69/.66/1.14 m
Gated standard	27/26/44.75 in	.69/.66/1.14 m
Power		
Power source - DC models	12V DC 110/50-60 Hz or 220/50-60 Hz AC	
Weight		
AC models (Standard)	777 lbs	352 kg

AWP-30S

- 35 ft 6 in (11.02 m) working height
- 29 ft 6 in (9.02 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- 1 ft 11 in (.58 m) narrow base width
- Up to 350 lbs (159 kg) lift capacity

Productivity

- Auxiliary platform lowering
- Most rigid mast in the industry
- Rocker base system for maneuverability
- Tilt back frame (standard on AWP™ -36, -40)
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt (ANSI / CSA only)
- Small outrigger footprints
- Outrigger storage sockets
- Easy loading in pickup trucks
- Tie down attachment points
- Overhead crane attachment point
- Wide, rear access forklift pocket
- LED lights confirm proper set-up

