




Self-Propelled Scissor Lifts

GS™ -2669 RT, GS-3369 RT, GS-4069 RT

Specifications



Models GS-3369 RT

Measurements	US	Metric
Working height maximum*	39 ft	11.9 m
A Platform height maximum	32 ft 8 in	9.96 m
B Platform height - stowed	4 ft 10 in	1.47 m
C Platform length - outside	9 ft 2 in	2.79 m
extended	14 ft 2 in	4.32 m
Slide-out platform extension deck	5 ft	1.52 m
D Platform width - outside	5 ft 3 in	1.6 m
Toeboard height	6 in	0.15 m
E Height - stowed**	8 ft 6 in	2.59 m
rails lowered	6 ft 3.5 in	1.92 m
F Length - stowed	10 ft 3 in	3.12 m
platform extended	14 ft 9 in	4.5 m
with outriggers	12 ft 4 in	3.76 m
G Width	5 ft 9 in	1.75 m
H Wheelbase	7 ft 6 in	2.29 m
I Ground clearance - center	9.5 in	0.24 m

Productivity

Maximum platform occupancy***	4	
Lift capacity	1,000 lbs	454 kg
Extension deck capacity	300 lbs	136 kg
Drive height	full height	
Drive speed - stowed	3.5 mph	5.6 km/h
Drive speed - raised	0.3 mph	0.5 km/h
Gradeability - stowed****	35%	
Maximum outrigger leveling:		
front/back uphill		
side to side		
Turning radius - inside	83 in	2.11 m
Turning radius - outside	181.2 in	4.6 m
Raise/lower speed	39 / 29 sec	
Controls		
Drive		
Tires - rough terrain	12 x 26 in	30 x 66 cm

Power

Power source	PSI (GM) .998L gas/LPG	
Fuel tank capacity	10 gal	37.9 L
Hydraulic system capacity	18 gal	68.1 L

Weight*****

	7,895 lbs	3,490 kg
--	-----------	----------

Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Based on RT tires; deduct 2 in (5.8 cm) for turf and non-marking tires.

*** Gradeability applies to driving on slopes. Gradeability may vary depending on the weight of options installed on machine.

See operator's manual for details regarding slope ratings.

**** Weight varies depending on options and country standards.

Features

Standard Features


Measurements

GS-3369 RT

- 39 ft (11.96 m) working height
- Up to 1,000 lbs (454 kg) lift capacity

Productivity

- Drive at full height
- 110 x 63 in (2.79 x 1.6m) steel frame platform with replaceable aluminum diamond plate deck
- 60 in (1.52 m) extension deck
- Folding rails
- Proportional lift and drive
- AC power to platform
- Full height swing gate
- 4WD
- Front oscillating axle
- Positive traction control
- Four-wheel braking
- Swing-out engine tray
- Foam-filled rough terrain tires
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter
- Motion alarm



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Effective Date: January, 2017. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2017 Terex Corporation.