

Specifications

Models	Z-34/22 DC	
Measurements	US	Metric
Working height maximum*	40 ft 6 in	12.52 m
Platform height maximum	34 ft 6 in	10.52 m
Horizontal reach maximum	22 ft 3 in	6.78 m
Up and over clearance maximum	15 ft	4.57 m
A Platform length	2 ft 6 in	0.76 m
B Platform width	4 ft 8 in	1.42 m
C Height - stowed	6 ft 7 in	2.00 m
D Length - stowed	18 ft 6 in	5.64 m
E Storage height	7 ft 5 in	2.26 m
F Storage length	13 ft 5 in	4.08 m
G Width	5 ft 8 in	1.73 m
H Wheelbase	6 ft 2 in	1.88 m
I Ground clearance - center	6 in	0.15 m

Productivity

Lift capacity	500 lbs	227 kg
Platform rotation	180°	
Vertical jib rotation	139°	
Turntable rotation	355° non-continuous	
Turntable tailswing	zero	
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised**	.68 mph	1.1 km/h
Gradeability - stowed***	30%	
Turning radius - inside	5 ft 9 in	1.75 m
Turning radius - outside	13 ft 1 in	4 m
Controls	24V DC proportional / 2 speed	
Tires - air filled	9 x 14.5 in	

Power


Power Source	48V DC (eight 6 V batteries 315 Ah capacity)	
Auxiliary Power Unit	24V DC	
Hydraulic Tank Capacity	4 gal	15.1 L
Fuel Tank Capacity	_____	_____

Weight****

11,000 lbs 4,990 kg 12,000 lbs 5,443 kg

Standards Compliance

ANSI A92.5, CSA B354.4, EN 280, AS 1418.10



* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** In lift mode *(platform raised), the machine is designed to operate on firm, level surfaces only.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.

Range Of Motion Z-34/22 DC

