

X700AJ

Platform Height	69' 7" (21.20 m)
Working Height	76' (23.16 m)
Horizontal Outreach	37' (11.27 m)
Swing	360° Non-continuous
Platform Capacity Restricted	440 lb (200 kg)
Platform Capacity Unrestricted	300 lb (136 kg)
Platform Rotation	124° (+/-62°)
Jib (Range of Articulation)	85° (-1/-86)
Platform Size Standard Two person	58" x 30" (1.47 x 0.76 m)
Optional Single person	31" x 24" (0.78 x 0.61 m)
Overall Width	39" (0.99 m)
Stowed Height With Pads	6' 6.5" (1.99 m)
Pads Detached	6' 6.5" (1.99 m)
Outrigger Footprint Narrow	15' 5" x 15' (4.69 m x 4.57 m) 9' 1" x 20' 4" (2.78 m x 6.19 m)
Stowed Length Without Basket	19' 8" (6.00 m) 18' 6" (5.64 m)
Track Length	5' 9" (1.77 m)
Weight*	7,050 lb (3,198 kg)
Ground Bearing Pressure Outriggers	43.07 psi (3.3 kg/cm ²)
Tracks	7.10 psi (.49 kg/cm ²)
Drive Speed	.80 mph (1.3 km/h)
Gradeability	40%
Slope Tolerance	14°
Gasoline Engine	Honda iGX440 15 hp (11.1 kW)
Electric Engine	100Ah 72V Lithium-Ion
Fuel Tank Capacity (Gasoline)	1.5 gal. (5.9 L)
AC Motor**	120V 60 Hz (1.2 kW)

*Certain options of country standards increase weight.

**Country specific options available.

X700AJ

